

May be used to comply with  
 OSHA's Hazard Communication Standard,  
 29 CFR 1910.1200. Standard Must Be  
 Consulted for Specific Requirements  
 IDENTITY (As Used on Label and List)  
 Printing Payons

*Recvd March 2002*

Occupational Safety and Health Administration  
 (Non-Mandatory Form)  
 Form Approved  
 OMB No. 1218-0072

*319-045/001308*

NOTE: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that

**SECTION I**

Manufacturer's Name <b>DXON TICONDEROGA</b>  Address( Number, Street, City, State, and ZIP)  1706 HAYES AVENUE SANDUSKY, OHIO 44870	Emergency Telephone Number	(419) 625-9545
	Telephone Number for Information	(419) 625-9545
	Date Prepared	2/22/2002
	Signature of Preparer (optional)	

**SECTION II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION**

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended %Optional
--	----------	-----------	---------------------------------------

Products bearing the CP Certified Products or AP Approved Products seals of the Art and Creative Materials Institute, Inc. are certified in a program of Toxicological evaluation by a Medical expert, subject to review by the Institute's Toxicological Advisory Board, to contain no materials in sufficient quantities to be toxic or injurious to humans or cause acute or chronic health problems.

CONFORMS TO ASTM-4236

**SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS**

Boiling Point	NA	Specific Gravity (H <sub>2</sub> O = 1)	NA
Vapor Pressure (mm Hg)	NA	Melting Point	NA
Vapor Density (Air=1)	NA	Evaporation Rate (Butyl Acetate = 1)	NA
Solubility In Water	NA		
Appearance and Odor	Assorted colors, 3 1/2" X 5 1/16" diameter, no odor.		

**SECTION IV - FIRE AND EXPLOSION HAZARD DATA**

Flash Point (Method Used)	NA	Flammable Limits	NA	LEL	UEL
Extinguishing Media	Water Spray, Foam, CO2		NA	NA	NA

Special Fire Fighting Procedures  
 Containers may be subject to ignition by fire and may release toxic or other irritating gases

Unusual Fire and Explosion Hazards  
 A self contained breathing apparatus should be used for this exposure.  
 (Reproduce Locally)

OSHA 174, SEPT. 1986

**SECTION V - REACTIVITY DATA**

Stability	Unstable	Conditions To Avoid	NONE
	Stable		
Incompatibility (Materials To Avoid)		NONE	

Hazardous Decomposition or Byproducts  
As with all burning organic matter, Carbon Monoxide and other toxic fumes may be given off.

Hazardous Polymerization	May Occur	Conditions To Avoid	NONE
	Will Not Occur		

**SECTION VI - HEALTH HAZARD DATA**

Route(s) Of Entry:	Inhalation?	Skin?	Ingestion?
	NO	YES	YES

Health Hazards (Acute and Chronic) Conforms to ASTM D-4236

Carcinogenicity:	NIH?	IARC Monographs?	OSHA Regulated?
	N/A		N/A

Signs and Symptoms of Exposure N/A

Medical Conditions Generally Aggravated by Exposure N/A

Emergency and First Aid Procedures  
Eyes—flush with copious amounts of water and contact a physician  
Contact with skin—Wash area with soap and water; Ingestion—seek medical attention;

**SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE**

Steps to Be Taken in Case Material Is Released or Spilled

Waste Disposal Method Contain and place in approved containers.

Precautions to Be Taken in Handling and Storing Dispose of per all Local, State, and Federal Regulations.

Other Precautions Do not store near heat or open flame.

Other Precautions None

**SECTION VIII - CONTROL MEASURES**

Respiratory Protection (specify Type) N/A

Ventilation	Local Exhaust	Special
	Mechanical (General)	Other

Protective Gloves	N/A	Eye Protection	YES
-------------------	-----	----------------	-----

Other Protective Clothing or Equipment N/A

Work/Hygenic Practices Contents will stain most fabrics, use of smocks, gloves, etc to protect personnel clothing is suggested. Wash hands and surfaces after use.